

HR型套筒式滚子链链轮的尺寸

(mm)

链号	齿数 N.T.	节距直径 P.C.D. (mm)	外径O.D.			孔径(B)		凸缘		重量		
			R (mm)	F (mm)	S (mm)	基孔	最大值	直径 (D)	宽度 (L)	R (kg)	F (kg)	S (kg)
HR6608	8	173.2	-	-	189	30	70	110	70	-	-	7.2
	9	193.8	-	-	210	30	70	115	70	-	-	8.8
	10	214.4	-	-	230	30	70	115	70	-	-	10.0
	11	235.2	-	-	251	30	75	120	80	-	-	12.0
	12	256.0	-	-	272	30	75	120	80	-	-	14.0
	14	297.8	-	-	314	30	75	120	80	-	-	17.0
	16	339.7	-	-	356	30	75	120	80	-	-	19.6
	18	381.6	-	-	398	30	80	125	90	-	-	22.0
	20	423.6	-	-	440	30	80	125	90	-	-	24.0
	22	465.7	-	-	482	30	80	130	90	-	-	27.0
HR7813	8	204.1	-	-	227	30	70	115	80	-	-	10.5
	9	228.4	-	-	251	30	70	115	80	-	-	12.5
	10	252.8	-	-	276	30	75	120	80	-	-	15.0
	11	277.3	-	-	300	30	75	120	85	-	-	18.5
	12	301.8	-	-	325	30	75	120	85	-	-	20.0
	14	351.2	-	-	374	30	80	130	85	-	-	24.0
	16	400.4	-	-	423	30	85	140	100	-	-	30.0
	18	449.1	-	-	473	30	85	140	100	-	-	34.0
	20	499.3	-	-	522	30	85	140	100	-	-	41.0
	22	548.8	-	-	572	40	90	145	100	-	-	50.0
HR10007	6	200.0	207	207	215	30	70	115	70	7.0	6.7	6.7
	8	261.3	275	275	276	30	75	120	80	11.8	11.4	11.4
	9	292.4	308	308	307	30	75	120	80	14.0	13.5	13.5
	10	323.6	341	341	339	30	75	120	80	15.3	14.7	14.7
	11	355.0	374	374	370	30	80	125	80	17.7	17.0	17.1
	12	386.4	407	407	401	30	80	125	90	18.0	18.0	18.1
	14	449.4	472	472	464	30	80	130	90	22.4	21.6	21.7
	16	512.6	536	536	528	30	85	140	100	27.6	26.7	26.8
	18	575.9	601	601	591	30	85	140	100	32.3	31.3	31.4
	20	639.3	665	665	654	40	95	150	100	38.4	37.2	37.8
HR10105	6	203.2	206	-	218	40	60	95	65	5.5	-	6.2
	8	265.5	279	-	281	40	65	100	70	10.8	-	10.6
	9	297.1	313	-	312	40	65	100	70	14.2	-	12.3
	10	328.8	346	-	344	40	70	115	80	16.0	-	15.5
	11	360.6	380	-	376	40	70	115	80	17.2	-	16.2
	12	392.6	413	-	408	40	70	115	80	18.4	-	18.0
	14	456.6	479	-	472	40	75	120	85	21.5	-	22.2
	16	520.8	544	-	536	40	80	130	90	27.0	-	27.2
	18	585.1	610	-	600	40	80	130	90	30.0	-	30.5
HR10108	6	203.2	221	221	219	40	70	115	70	9.5	8.7	8.3
	8	265.5	291	291	282	40	75	120	80	14.8	17.0	13.8
	9	297.1	325	325	313	40	75	120	80	16.2	14.9	16.1
	10	328.8	358	358	345	40	75	120	80	20.0	18.0	18.1
	11	360.6	392	392	377	40	80	125	80	22.5	20.5	20.5
	12	392.6	425	425	409	40	80	125	90	25.4	23.4	22.0
	14	456.6	489	489	473	40	80	130	90	30.5	27.4	26.5
	16	520.8	553	553	537	40	85	140	100	33.5	31.5	33.5
	18	585.1	617	617	601	40	85	140	100	40.5	36.5	38.0
20	649.5	682	682	666	40	95	150	100	49.0	40.0	45.5	

注: 凸缘的形式全为“C”。