

HR 型套筒式滚子链链轮的尺寸

(mm)

链号	齿数 N.T.	节距直径 P.C.D. (mm)	外径 O.D.			孔径(B)		凸缘		重量		
			R (mm)	F (mm)	S (mm)	基孔	最大值	直径 (D)	宽度 (L)	R (kg)	F (kg)	S (kg)
HR10113	6	203.2	235	-	226	40	75	120	85	11.0	-	9.1
	8	265.5	298	-	289	40	80	130	90	17.6	-	16.7
	9	297.1	329	-	320	40	80	130	90	21.6	-	20.0
	10	328.8	361	-	352	40	85	135	95	24.7	-	23.0
	11	360.6	393	-	384	40	90	145	100	31.5	-	27.5
	12	392.6	425	-	416	40	90	145	100	32.5	-	30.5
	14	456.6	489	-	480	40	95	150	105	36.5	-	36.0
	16	520.8	553	-	544	50	100	160	110	48.0	-	46.0
	18	585.1	617	-	608	50	105	165	115	55.5	-	52.5
20	649.5	682	-	673	50	105	165	115	65.0	-	60.5	
HR15011	6	300.0	305	305	320	30	80	130	90	19.0	16.5	19.2
	8	392.0	408	408	412	40	90	145	100	31.5	26.5	32.0
	9	438.6	458	458	458	40	90	145	100	35.0	28.7	36.3
	10	485.4	507	505	505	40	95	150	105	39.5	30.0	40.5
	11	532.4	556	556	552	40	95	150	105	45.0	32.5	45.5
	12	579.6	605	605	600	40	100	160	110	52.5	38.5	53.0
	14	674.1	703	703	694	50	105	165	115	62.5	52.5	64.0
	16	768.9	800	800	788	50	105	170	120	76.0	69.5	78.1
HR15208	6	304.8	317	317	323	30	70	115	80	18.7	14.6	18.1
	8	398.2	421	421	416	30	75	120	85	26.0	22.1	27.4
	9	445.6	472	472	464	30	80	130	90	29.2	24.8	29.6
	10	493.2	523	523	511	30	85	135	95	35.0	30.0	37.0
	11	540.9	573	573	559	30	85	135	95	38.0	34.0	38.0
	12	588.8	622	622	607	40	90	145	100	43.0	38.0	43.0
	14	684.9	721	721	703	40	95	150	105	56.5	50.5	55.5
	16	781.2	817	817	799	40	95	150	105	64.5	63.5	64.5
HR15215	6	304.8	329	329	330	40	90	145	100	28.0	25.0	23.3
	8	398.2	433	433	423	40	95	150	105	36.0	32.0	36.5
	9	445.6	484	484	471	40	100	160	110	40.0	34.0	45.5
	10	493.2	534	534	518	40	100	160	110	44.0	37.0	51.0
	11	540.9	582	582	566	40	100	160	115	60.0	42.5	57.7
	12	588.8	630	630	614	50	105	170	120	64.0	56.5	67.5
	14	684.9	726	726	710	50	115	180	125	77.0	68.0	79.5
	16	781.2	822	822	806	50	115	185	130	93.0	81.0	92.5
HR15219	6	304.8	343	-	333	40	95	150	105	26.0	-	25.0
	8	398.2	447	-	426	50	105	165	115	43.5	-	41.5
	9	445.6	496	-	474	50	105	165	115	49.5	-	50.5
	10	493.2	543	-	521	50	105	170	120	53.0	-	53.5
	11	540.9	591	-	569	50	115	180	125	61.0	-	59.5
	12	588.8	639	-	617	50	115	180	125	68.0	-	67.5
	14	684.9	735	-	713	50	115	185	130	82.0	-	79.5
	16	781.2	831	-	809	50	125	200	140	103.0	-	100.0
HR20015	6	400.0	412	412	425	40	95	150	105	37.5	31.5	36.5
	8	522.6	548	548	548	50	105	165	115	57.0	45.0	49.0
	9	584.8	615	610	610	50	105	165	115	65.0	50.0	58.5
	10	647.2	681	681	672	50	105	115	115	75.0	63.0	64.0
	11	709.9	747	747	735	50	115	180	125	85.0	74.0	74.0
	12	772.7	812	812	798	50	115	185	130	96.0	81.5	82.0
	14	898.8	942	942	924	50	115	185	130	115.0	103.0	104.0
HR20019	6	400.0	426	426	428	40	100	160	105	47.5	40.5	50.8
	8	522.6	562	562	551	40	100	160	105	73.5	64.0	72.5
	9	584.8	629	629	613	50	105	170	110	83.5	73.0	80.0
	10	647.2	695	695	675	50	105	170	110	89.5	80.5	90.0
	11	709.9	761	761	738	50	105	170	110	105.0	92.0	100.0
	12	772.2	826	826	801	50	115	180	115	114.0	110.0	110.0
	14	898.8	956	956	927	50	115	180	115	125.0	128.0	137.0

注: 凸缘的形式全为“C”。