

HR 型套筒式滚子链链轮的尺寸

(mm)

链号	齿数 N.T.	节距直径 P.C.D. (mm)	外径 O.D.			孔径(B)		凸缘		重量		
			R (mm)	F (mm)	S (mm)	基孔	最大值	直径 (D)	宽度 (L)	R (kg)	F (kg)	S (kg)
HR25015	6	500.0	505	505	525	40	100	160	110	51.0	44.0	56.0
	8	653.0	669	669	678	50	105	170	120	72.0	62.0	80.0
	9	731.0	752	752	756	50	115	180	125	94.0	72.0	91.0
	10	809.0	835	835	834	50	115	185	130	100.0	89.0	106.0
	11	887.4	917	917	912	50	115	185	130	121.0	100.0	122.0
HR25019	6	500.0	513	513	528	50	105	170	120	67.0	60.0	70.0
	8	653.0	683	683	681	50	115	185	130	93.0	90.0	100.0
	9	731.0	766	766	759	50	120	195	135	111.0	110.0	119.0
	10	809.0	849	849	837	50	125	200	140	133.0	125.0	135.0
	11	887.4	931	931	915	50	130	210	150	149.0	140.0	154.0
HR25026	6	500.0	-	-	532	50	120	190	135	-	-	84.0
	8	653.3	-	-	685	50	125	200	140	-	-	114.0
	9	731.0	-	-	763	50	125	200	140	-	-	122.0
	10	809.0	-	-	841	60	140	220	155	-	-	155.0
	11	887.4	-	-	919	60	140	225	160	-	-	173.0
HR30019	6	600.0	628	606	628	50	115	180	125	89.0	79.0	90.0
	8	783.9	804	804	812	50	125	200	140	128.0	122.0	131.0
	9	877.1	904	904	905	50	125	200	140	145.0	136.0	147.0
	10	970.8	1,003	1,003	999	50	130	210	150	173.0	160.0	174.0
	HR30026	6	600.0	619	619	632	50	125	200	140	108.0	92.0
7		691.4	722	722	723	60	140	200	155	137.0	128.0	138.0
8		783.9	824	824	816	60	140	220	155	160.0	137.0	166.0
9		877.1	924	924	909	60	140	220	155	185.0	166.0	198.0
10		970.8	1,023	1,023	1,003	60	145	235	165	210.0	195.0	214.0
HR30048	6	600.0	-	-	636	60	130	210	150	-	-	137.0
	7	691.4	-	-	727	60	140	220	150	-	-	165.0
	8	783.9	-	-	820	60	140	220	150	-	-	192.0
	9	877.1	-	-	913	60	145	230	160	-	-	224.0
	10	970.8	-	-	1,007	60	150	240	165	-	-	254.0
HR30054	6	600.0	-	-	641	60	140	220	160	-	-	154.0
	8	783.9	-	-	825	60	150	240	170	-	-	223.0
HR45026	6	900.0	971	971	932	50	125	200	150	187.0	162.0	188.0
	8	1,175.9	1,247	1,247	1,208	50	125	200	160	276.0	235.0	280.0
HR45048	6	900.0	989	989	936	60	140	220	160	218.0	177.0	222.0
	8	1,175.9	1,265	1,265	1,212	60	155	250	180	325.0	287.0	334.0
HR45054	6	900.0	1,000	1,000	941	60	145	230	165	246.0	208.0	256.0
	8	1,175.9	1,276	1,276	1,217	60	160	255	180	368.0	319.0	384.0
HR60048	6	1,200.0	1,289	1,289	1,236	60	160	255	180	347.0	297.0	368.0
	8	1,567.0	1,657	1,657	1,604	60	160	255	180	497.0	402.0	552.0
HR60054	6	1,200.0	1,300	1,300	1,241	70	175	280	195	399.0	356.0	438.0
	8	1,567.9	1,668	1,668	1,609	70	190	305	215	635.0	514.0	721.0

注: 凸缘的形式全为“C”。